

D6500 打印光机

Display technique	0.65" inch DMD
Resolution	1920*1080
Light source	UV405 LED/UV385LED
Light channel	Singe channel
Brightness	2.5W @50W; 3.0W@70W;
Focus	19 to 23
Contrast	1500 : 1
Uniformity	>90%
Distortion	<0.12%
Pixel size	96x54@0.05mm, 160x90@0.083mm
Offset	Without offset
Power supply	DC 12V/5A
Total power	<60W
Dimension	L210*W120*H130 (mm) L210*W158*H130 (mm)[含镜头]
Material	Body: All metal; Optics: All glass;
Input interface	HDMI x1
	Mini USB x1
Software	Power Soft switch,LED onoff,LED Exposure Current Adjust
	Image Short-Axis and Long-Axis Image Flip
	Windows/Linux 32,64-bit OS platform SDK support
	Custom Logo, and Other requirements

Image size VS Distance (mm)

Resolution	Image size		Distance	
	W	H	Min	Max
0.05	96	54	96	122
0.06	115	65	122	155
0.07	134	76	149	187
0.08	154	86	175	220
0.09	160	90	188	230

此款光机是变焦镜头，最佳打印尺寸 96X54 到 144X81，打印距

离 96-200，打印精度 50-80（微米）。

这是打印大尺寸

Image size vs Distance

Resolution	Image size		Distance (WD)	
	W (mm)	H (mm)	min (mm)	max (mm)
0.10mm	192	108	221	265
0.11mm	211.2	118.8	245	300
0.12mm	230.4	129.6	273	330
0.13mm	249.6	140.4	300	366
0.14mm	268.8	151.2	326	390
0.15mm	288	162	350	425

扫描（取掉垫片）：最近距离 30 公分 扫描面积 20.3X11.4,最远 120 公分，
扫描面积 91.3X51.3



上海意仪电子科技有限公司
shanghaiyiyidianshijieyouxiangongsi



刘利 liuli
DLP 系列产品销售工程师

15618587576/15921998772
15618587576@163.com
021-64642232
021-64642232
上海市徐汇区漕宝路 36 号和诚
商务大厦 2 号楼 408 室



3D 扫描 3D 在线检测 3D 打印 光刻 A0I 自动光学检测 SPI 锡膏检测 PIN 背板检测 IC 引脚翘曲共面检测 锂电池检测 手机零部件检测等



<http://www.yiyill.icoc.me/>